

Deck Type I:

Wood, Non-Insulated
1/2" or greater plywood or wood plank decks

Deck Description:
Base sheet mechanically fastened.

System Type E (1):
All General and System Limitations shall apply.

Base sheet:
GAFGLAS #80 RUBEROD Modified Base Sheet, RUBEROD #75 RUBEROD
SBS Heat-Welded Smooth or RUBEROD SBS Heat-Weld 15 base sheet
mechanically fastened to deck as described below;

Fastening Options:

GAFGLAS® Ply 40, GAFGLAS Flex Ply™ 6, GAFGLAS #75 Base Sheet or any of above Base sheets attached to deck with approved annular ring shank nails and tin caps at a stagger spacing of 9" o.c. at the lap staggered and in two rows 12" o.c. in the field.
(Maximum Design Pressure -45 psf. See General Limitation #7)
GAFGLAS® Ply 40, GAFGLAS Flex Ply™ 6, GAFGLAS #75 Base Sheet or any of above Base sheets attached to deck with Drill-Tec (GAFITE) #12 or #14 Screws and 3" Plates, 12" o.c. in the field of the sheet. The other rows are equally spaced approximately 12" o.c. in the field of the sheet.
(Maximum Design Pressure -45 psf. See General Limitation #7)
GAFGLAS® Ply 40, GAFGLAS Flex Ply™ 6, GAFGLAS #75 Base Sheet or any of above Base sheets attached to deck with approved annular ring shank nails and tin caps at a stagger spacing of 9" o.c. at the 4" lap staggered and in two rows 9" o.c. in the field.
(Maximum Design Pressure -52.5 psf. See General Limitation #7)
GAFGLAS® Ply 40, GAFGLAS Flex Ply™ 6, GAFGLAS #75 Base Sheet or any of above Base sheets attached to deck with Drill-Tec (GAFITE) #12 or #14 Screws and 3" Plates, 12" o.c. in 4 rows. One row is in the 2" side lap. The other rows are equally spaced approximately 9" o.c. in the field of the sheet.
(Maximum Design Pressure -60 psf. See General Limitation #7)
Any of above Base sheets attached to deck approved annular ring shank nails and 3" insulating plates at a stagger spacing of 9" o.c. at the 4" lap staggered and in two rows 9" o.c. in the field of the sheet. The other rows are equally spaced approximately 9" o.c. in the field of the sheet.
(Maximum Design Pressure -60 psf. See General Limitation #7)
GAFGLAS® Ply 40, GAFGLAS Flex Ply™ 6, GAFGLAS #75 Base Sheet or any of above Base sheets attached to deck with Drill-Tec (GAFITE) #12 or #14 Screws and 3" Plates, 8" o.c. in 4 rows. One row is in the 2" side lap. The other rows are equally spaced approximately 9" o.c. in the field of the sheet.
(Maximum Design Pressure -75 psf. See General Limitation #7)
One ply of GAFGLAS® Ply 40, GAFGLAS Flex Ply™ 6, GAFGLAS #75 Base Sheet, #80 RUBEROD MOP Smooth or RUBEROD #75 RUBEROD MOP adhered in a full mopping of approved asphalt applied within the EVT range and at a rate of 20-40 lbs./sq.
(Optional) One ply of GAFGLAS® Mineral Surfaced Cap Sheet adhered in a full mopping of approved asphalt applied within the EVT range and at a rate of 20-40 lbs./sq.

Ply Sheet:

Cap Sheet:



NOA No. 03-0501.05
Expiration Date: 11/04/08
Approval Date: 10/23/03
Page 18 of 21